

## 2K Anti Silicone Additive

### Product description

Anti-silicone solution for 2K additives.

### Products

222

### Note

Information contained herein is based on careful investigation and is intended for information only. User is obliged to test the suitability of the products for their particular use. Supplier may change any specifications without notice.

### Uses

Solvent borne products in need of level enhancement.

*The EU limit value for this product (product category: 2004/42 IIB In ready to use form is max. 840g/litre of VOC.*

Composition	Liquid
Colour	Water – white liquid
Shelf life	18 months in unopened container
Pack Size	500ml

	<h3><u>Health and Safety</u></h3> <p>"For professional use only" Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.</p>
	<h3><u>Tools Required</u></h3> <p>Mixing stick Additive bottle with working reservoir Premium mask/gloves Painter's overalls</p>
	<h3><u>Cleaning</u></h3> <p>Clean all tools thoroughly before and after use. Clean and degrease removing dirt, oil, grease and wax before and after using. Use a degreaser if necessary.</p>
	<h3><u>Application</u></h3> <p>Loosen cap and squeeze bottle. Squeeze the container gently to fill the reservoir to the desired level then add to product, mixing well. Recommended quantity is 10ml per 500ml of product. Apply the product with the added additive to the substrate in the standard procedure you would normally.</p>