

1K Plastic Primer

Product description

Air drying, one-pack primer to promote the adhesion on plastic car body parts.

Products

PP1 Plastic Primer

Note

Product should be at 20°C prior to use.

Information contained herein is based on careful investigation and is intended for information only. User is obliged to test the suitability of the products for their particular use. Supplier may change any specifications without notice.


The EU limit value for this product (product category IIB.e) in ready to use form is max. 840 g/litre of VOC. The VOC content of this product in ready to use form is max. 780 g/litre - 2004/42/IIB.e(840)780

Composition	Solvent blend and resin
Colour	Clear (slight tinge)
Shelf life	24 months in unopened container
Pack Size	1 litre

Pre-treatment

Clean substrate (without OEM primer) with warm water and detergent. Degrease and Scuff surface with Scotch Brite VF (Grey) then Degrease and tack rag off, getting a dry clean surface.

	<h3><u>Health and Safety</u></h3> <p>"For professional use only" Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.</p>
	<h3><u>Mix Ratio</u></h3> <p>Ready to use.</p>
	<h3><u>Spraying viscosity</u></h3> <p>As supplied</p> <h3><u>Pot life</u></h3> <p>24 hours</p>

	<u>Application</u>			
	Spray Gun	Fluid tip size	Working pressure	
		1.2-1.4 mm	2.0-2.2 bar	
	1 Dust coat to cover			
	<u>Drying</u>	All force dry/infrared times operate @ 60°C Metal 80°C Air		
	Instant dry.			